

■ **Features :**

- Green design, No-load power consumption < 0.3W
- Universal AC input / Full range
- Protections: Short circuit / Over load / Over voltage
Brown-out (Low AC Input voltage)
- Medical safety approved
- Fully isolated plastic case
- Isolation class II
- All using 105°C long life electrolytic capacitors
- High operation temperature up to 70°C
- 100% full load burn-in test
- Withstand 2G vibration test
- Cooling by free air convection
- 3 years warranty




MODEL		ME-15-05	ME-15-12	ME-15-15	ME-15-24
OUTPUT	DC Voltage Range	5V	12V	15V	24V
	Rated Current	3A	1.25A	1.0A	0.63A
	Current Range	0 ~ 3A	0 ~ 1.25A	0 ~ 1.0A	0 ~ 0.63A
	Rated Power	15W	15W	15W	15.12W
	Ripple & Noise (max.)	80 mv	150 mv	150 mv	240 mv
	Voltage Tolerance	+5 / -3%			
	Line Regulation <small>Note.8</small>	±1%	±0.5%	±0.5%	±0.5%
	Load Regulation <small>Note.8</small>	±1%	±0.5%	±0.5%	±0.5%
	Setup, Rise Time	100ms, 25ms/230VAC 100ms, 25ms/115VAC at full load			
Hold Up Time	100ms / 230VAC 25ms / 115VAC at full load				
INPUT	Voltage Range	85V ~ 264VAC	125 ~ 373VDC		
	Frequency Range	47Hz ~ 63Hz			
	Efficiency (Typ.) at 230Vac	79%	82%	84%	85%
	AC Current (Typ.)	0.35 A / 115VAC 0.2A / 230VAC			
	Inrush Current (Typ.)	Cold Start 30A / 115VAC 50A / 230VAC			
Protection	Over Load	Above 110% rated output power Protection type : Hiccup mode, recovers automatically after fault condition is removed			
	Over Voltage	115% ~ 145% rated output voltage Protection type : latch-off mode			
Environment	Working Temp.	-20°C ~ 70°C (Refer to output load de-rating curve)			
	Working Humidity	20 ~ 90% RH non-condensing			
	Storage Temp., Humidity	-40 ~ +85°C, 10 ~ 95% R.H			
	Temp. Coefficient	±0.03%/°C (0 ~ 50°C)			
Safety & EMC	Vibration	10 ~ 500Hz, 2G 10min/1cycle, period for 60 min each along X,Y,Z axes			
	Safety Standards	UL60601-1 / TUV EN60601-1 / IEC60601-1 Approved			
	Withstand Voltage	I/P - O/P: 4KVAC			
	Isolation Resistance	I/P - O/P : 100M Ohms / 500VDC			
	EMI Conduction & Radiation	EN55011: 2007+A2: 2007 Class B			
	Harmonic Current	EN61000-3-2: 2006 Class A, EN61000-3-3: 1995+A1: 2001+A2: 2005			
Others	EMS Immunity	EN60601-1-2: 2001+A1: 2006, IEC61000-4-2,3,4,5,6,8,11 light industry level, criteria A			
	MTBF	206.3K HRS Compliance: MIL-HDBK-217F			
	Dimension (L*W*H)(mm)	75x53x22.7			
Note	Packing	0.14kg ; 120Pcs/16.8kg			
		1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47 uf parallel capacitor. 3. Tolerance: includes set up tolerance, line regulation and load regulation. 4. Line regulation is measured from low line to high line at rated load. 5. Load regulation is measured from 10% to 100% rated load. 6. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives. 7. Length of set up time is measured at cold first start. Turning ON/OFF the power supply very quickly may lead to increase of the set up time 8. The line regulation and load regulation is calculated based on output voltage.			




■ Mechanical Specification

Unit:inch(mm)




■ Block Diagram



■ De-rating Curve

Load V.S Temp.



Load V.S I/P Voltage

